

120 TOP Series

Cold, room and sparkling water.

Equipment for restaurants and restaurants.

Table-top dispenser. Steel-inox.

120 lph
Cold water production



SPECIFICATIONS:

Production: 120 l/h.
 Continuous production: 70 l.
 Temperature: 3 - 10 °C.
 Ice bank capacity: 6,5 Kg.
 Cooling sparkling: R290.
 Compressor power: 1/3 CV.
 Water outputs HG:
 3 (1 cold, 1 room, 1 sparkling).
 Water outputs HF:
 3 (1 cold, 1 room, 1 cold).
 Water inlet connection: 8 mm.
 *Sparkling inlet connection: 8 mm.
 Materials: Stainless steel.
 Weight: 40-48 Kg (according to model).

*Only models HG

Accessories:


Adaptor H3/4" - Stem 8 mm.
 Elbow 8 mm.
 Adaptor M3/8" - 8 mm.
 2 m tube 8 mm.
 *Pressure reducer CO₂.



B1. Basic Tray



B2. Tray with drain



Model	Room	Cold	Sparkling	Volume regulation	Electronical	Mechanical	Touchless	Tray
980015 HG 120 E TOP B1	•	•	•	•	•			B1
980392 HG 120 E TOP B2	•	•	•	•	•			B2
980014 HG 120 TOP B1	•	•	•			•		B1
980013 HG 120 TOP B2	•	•	•			•		B2
980645 HG 120 E TOP TOUCHLESS B1	•	•	•	•	•		•	B1
980646 HG 120 E TOP TOUCHLESS B2	•	•	•	•	•		•	B2
980648 HG 120 TOP TOUCHLESS B1	•	•	•			•	•	B1
980649 HG 120 TOP TOUCHLESS B2	•	•	•			•	•	B2
980012 HF 120 E TOP B1	•	•		•	•			B1
980394 HF 120 E TOP B2	•	•		•	•			B2
980011 HF 120 TOP B1	•	•				•		B1
980010 HF 120 TOP B2	•	•				•		B2
980651 HF 120 E TOP TOUCHLESS B1	•	•		•	•		•	B1
980622 HF 120 E TOP TOUCHLESS B2	•	•		•	•		•	B2
980611 HF 120 TOP TOUCHLESS B1	•	•					•	B1
980653 HF 120 TOP TOUCHLESS B2	•	•					•	B2

980043 Centering device for 3 bottles