

RO COMERCIAL COLUMBIA AQUA 2000G

(Ref. 796221)

FEATURES

RO WATER PRODUCTION	5 l/min.
RO MEMBRANES	2 x 3313 membrane of 1000 GPD
PRESSURE SYSTEM	Pump 600 l/h
PRODUCTION MAX.	4000 l/day - 166 l/hour.
ELECTRICAL POWER SUPPLY	220-240 VAC, 50 Hz
LEAKAGE PROTECTION	Aquastop leaking sensor
INLET PRESSURE	3 - 6 bar.
INLET TEMPERATURE	4 - 40 °C
DIMENSIONS	660 x 265 x 530 mm




INPUT CONNECTIONS

INLET	DRAIN	PRODUCTION
3/8" tube	3/8" tube	3/8" tube

COMPONENTS

3 x LOGIC AQUA PREMIUM 17" carbon pre-filters
2 x 1000 GPD 3313 type osmosis membranes



WLG (B-60326279), is member of the Water Quality Association.



ACCREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.