


ERGO 8 & 11

CODE	MODEL
902803	Compact softener ERGO 8
902829	Compact softener ERGO 11



	ERGO 8	ERGO 11
• Code	902803	902829
• Resin volume	7,4 liters	10,5 liters
• Operational water flow	1,8 m³/h	2,1 m³/h
• Maximum water flow	2,1 m³/h	2,1 m³/h
• Exchange volume	17,6°HFxm³	23,7°HFxm³
• Salt/regeneration	0,36 Kg Salt	0,36 Kg Salt
• Maximum hardness	60 °HF	73 °HF
• Drained water/reg.	25	
• Regeneration time	15 minutes	
• Temperature protection system	Anti-freeze protection	
• Temperature range	1,7 - 45°C	
• Pressure range	1,7 - 8,6 bar	
• Dimensions (a x b x c)	508 x 500 x 293	608 x 500 x 297



Uses less water



Non electrical  
softener



High water flow



Just 15 minutes  
regeneration



Low salt consumption

ERGO 8

15°HF	20°HF	25°HF	30°HF	35°HF	40°HF	50°HF	60°HF
914	685	548	457	392	343	274	228

ERGO 11

15°HF	20°HF	25°HF	30°HF	40°HF	50°HF	60°HF	70°HF
1250	938	750	625	469	375	313	268



Puricom Water Industrial Corporation and Ionfilter (B-60326279) are members of Water Quality Association.



The quality system of Ionfilter (B-60326279) for the commercialization of water treatment equipment and appliances. Design and delivery of non-regulated training related to the technology of commercialized equipment is certified and fulfills the requirements of the norm UNE-ISO-9001.



Puricom Europe belong to Aqua Spain's group, member of Aqua Europe (European national associations federation)

