

→ Water softener

# RIDER 12

(Ref.795252)

## SPECIFICATIONS

RESIN VOLUME	12 liters
BOTTLES	10x15
WORK FLOW	1m <sup>3</sup> /h
MAXIMUM FLOW	1,5m <sup>3</sup> /h
MAXIMUM TEMPERATURE	120°HF

LOW CAPACITY CONFIG.	
SALT/REGENERATION	0,8 kg salt
EXCHANGE CAPACITY	40°HFxm <sup>3</sup>

MEDIUM CAPACITY CONFIG.	
SALT/REGENERATION	1 kg salt
EXCHANGE CAPACITY	49°HFxm <sup>3</sup>

HIGH CAPACITY CONFIG.	
SALT/REGENERATION	1,5 kg salt
EXCHANGE CAPACITY	60°HFxm <sup>3</sup>
MINIMUM FLOW	0,1m <sup>3</sup> /h
TEMPERATURE RANGE	4-35°C
PRESSURE RANGE	2,5- 8 bar
PRESSURE CLASIFICATION	8 bar
POWER SUPPLY	220V/50Hz-24VAC
NOMINAL POWER	4 W
PROTECTION TYPE	TYPE III


-  ELECTRONIC PROGRAMMER
-  MIXING VALVE
-  INTEGRATED BY-PASS
-  MULTILINGUAL PROGRAMMER



LOW CAPACITY : 96°HFxm <sup>3</sup>						
15°HF	25°HF	30°HF	35°HF	45°HF	55°HF	
3,20	1,92	1,60	1,37	1,06	0,75	

MEDIUM CAPACITY : 141°HFxm <sup>3</sup>						
15°HF	25°HF	30°HF	35°HF	45°HF	55°HF	
4,7	2,82	2,35	2,0	1,55	1,28	

HIGH CAPACITY : 175°HFxm <sup>3</sup>						
15°HF	25°HF	30°HF	35°HF	45°HF	55°HF	
5,83	3,5	2,91	2,5	1,94	1,59	



ACCREDITED BY ENAC  
Certif. nº 34/5200/14/0712



WLG (B-60326279), is member of the Water Quality Association.

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).

WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).

WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.