

→ Reverse osmosis

RO ÍNDIKA

(Ref.910692)

Direct Flow system

SPECIFICATIONS

MANUALIM ELON	4.5.1
MAXIMUM FLOW	1,5 lpm
WEIGHT	8,5kg
INLET TEMPERATURE (maxmin.)	38°C / 5°C
INLET TDS	1500 ppm
INLET PRESSURE	4 bar - 1 bar (400kPa-100kPa)
PREFILTER	combi 5 micron pp + high quality block carbon
MEMBRANE	600GPD
FAUCET	Smart faucet
PUMP	Booster pump
POWER SUPPLY	24 Vdc
ADAPTER	100-240V. 50/60Hz: 24Vdc 4A



DIRECT FLOW



EXCLUSIVE MEMBRANE



FILTER CONTROL



SOUND WARNINGS



SMART FAUCET



LED STATUS




HIGH EFFICIENCY



ORIGINAL CONSUMABLES

Combinated filter. (Ref. 910693)	
Reverse osmosis membrane (Ref. 910694)	







WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).

NET PRICE







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).

WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.