

→ Reverse osmosis

RO REKA 800

(Ref.910452)

Direct Flow system

DESCRIPTION

Reverse Osmosis System.
Direct Flow.
Without water tank.
Low cost of maintenance.
Long life of filters and membrane.
Great design and versatility.

SPECIFICATIONS

WEIGHT	12 kg
FLOW	1,6 lpm / 2,1 lpm
TEMPERATURE (max min.)	38 °C - 5 °C
INLET TDS (max.)	1500 ppm
PRESSURE (max mmn.)	4 bar - 1 bar (400kPa - 100kPa)
MEMBRANE	800 GPD
FAUCET	faucet smart
POWER SUPPLY	24 Vdc / 36 Vdc
EXTERNAL ADAPTER	230 Vac 50 / 60 hz: 24 Vdc / 36 Vdc



Combi sediment + carbon block Black (cód. 910465)

RO Membrane 800GPD Black (cód. 910467)



FILTER CONTROL



QUALITY CONTROL



SOUND WARNINGS



LED STATUS



HIGH EFFICIENCY RECOVERY



AQUASTOP



SMART FAUCET



ELECTRONIC ADAPTER



401 mm



456





WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).







WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).