

CODE

903076

DESCRIPTION

TOREN 11 compact hydraulic
Water Softener



ASSEMBLY IN
EUROPE

SPECIFICATIONS

DIMENSIONS: (height x diameter): 678 mm x 356 mm

WEIGHT: 30 kg

RESIN VOLUME (l.): 10,5 liters

PRESSURE (MAX-MIN): 1,7- 8,6 bar

WORK FLOW: 2,1 m³/h

WORK MAXIMUM FLOW: 2,1 m³/h

MAXIMUM HARDNESS: 73°HF

INTERCHANGE CAPACITY: 23,7°HFxm³

SALT / REGENERATION: 0,36 kg sal

WATER CONSUMPTION / REG: 25 liters

REGENERATION TIME: 15 min

ROOM TEMPERATURE: Protection against freezing

TEMPERATURE RANGE: 2 - 40°C



NON ELECTRIC
No power supply
needed



SAVINGS
Less water
used



HIGH SPEED
Regeneration
in 15 min.




LOW
CONSUMPTION
Low salt
consumption



HIGH FLOW
Ideal for
your home

15°HF	20°HF	25°HF	30°HF	40°HF	50°HF	60°HF	70°HF
1250	938	750	625	469	375	313	268



WLG (B-60326279), is member of the
Water Quality Association.



ACCREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).



WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOP18000008U6 and 13/02/2018 as a date of entry of the authorization.