

CODE

DESCRIPTION

903075

TOREN 8 compact hydraulic Water Softener







ASSEMBLY IN EUROPE



DIMENSIONS: (height x diameter): 566 mm x 351 mm

WEIGHT: 20 kg

RESIN VOLUME (I.): 7,4 liters
PRESSURE (MAX-MIN): 2,5-8,6 bar

WORK FLOW: 1,8 m3/h

WORK MAXIMUM FLOW: 2,1 m³/h MAXIMUM HARDNESS: 60°HF

INTERCHANGE CAPACITY: 17,6°HFxm³
SALT / REGENERATION: 0,36 kg salt
WATER CONSUMPTION / REG: 25 liters

REGENERATION TIME: 15 min

ROOM TEMPERATURE: Protection against freezing

TEMPERATURE RANGE: 2 - 40°C

15°HF	20°HF	25°HF	30°HF	35°HF	40°HF	50°HF	60°HF
914	685	548	457	392	343	274	228



NON ELECTRIC
No power supply
needed



SAVINGS Less water






HIGH SPEED Regeneration in 15 min.



LOW CONSUMPTION Low salt consumption



HIGH FLOW Ideal for your home







WLG (B-60326279), is member of the Water Quality Association.



The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 far WLG (B-60326279).





WLG (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



WLG (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.